

NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

Prediction of Thermal Radiation from a Rocket's Exhaust Plume

The absorption coefficients and fine-structure parameters have been measured for water vapor at wavelengths between 1 and 10 μm at temperatures between 1,200° and 3,000°K. The resultant data have been incorporated in a practical analytic procedure that can be used for evaluation of heating by radiation from the exhaust plume of the base of a large rocket.

A uniform volume of high-temperature water vapor was produced above the combustion zone of a specially constructed long, 3-inch-wide, flat burner. Emission and absorption were measured, with path lengths of 2, 5, and 10 feet, at temperatures between 1,200° and 3,000°K. From these measurements mean absorption coefficients and fine-structure parameters (averaged over 25- cm^{-1} intervals) were deduced for the spectral interval between 1,000 and 9,000 cm^{-1} . The resultant data are presented in both graphic and tabular forms, with polynomial representations also.

Combination of these results with earlier data has generated tables of water-vapor absorption coefficients covering the spectral region between 50 and 9,300 cm^{-1} and the temperature range between 300° and 3,000°K; the representation of the fine-structure parameters covers the ranges between 1,150 and 9,300 cm^{-1} and 1,250° and 2,750°K.

Several nonisothermal measurements, with two 5-foot sections at different temperatures, were made

to test the nonisothermal-radiance calculation procedure. The following analytic studies were made: (1) extension of the high-pressure-limit calculation for the total engineering emissivity to self-broadened and nitrogen-broadened water vapor, with use of published absorption coefficients and band-averaged fine-structure parameters; (2) study of band models for randomly distributed Doppler lines; (3) an error and sensitivity analysis of the inhomogeneous-radiance calculation technique; and (4) study of an alternative expression for the collision-broadened line width.

Notes:

1. This information may interest personnel concerned with thermal radiation from gases.
2. Documentation is available from:
Clearinghouse for Federal Scientific
and Technical Information
Springfield, Virginia 22151
Price \$3.00
Reference: TSP69-10371

Patent status:

No patent action is contemplated by NASA.

Source: C. B. Ludwig et al. of
General Dynamics Corporation
under contract to
Marshall Space Flight Center
(MFS-20414)

Category 02